



XC936



HANLINK MOBILITY TANZANIA  Julius K. Nyerere Road, Dar es Salaam



+255 758 301 399 | **+255 764 228 228**

Email: benny@hanlinkgroups.com

kai.you@hanlink.com

Main Specifications

main components

Item	Parameter	Parameter
Rated bucket capacity m ³	2.1	1.8 (small-height dumping)
Rated load kg	3500	3000
Operating weight kg	10300±200	10400±200
Dumping height mm	2900	3240
Dumping range mm	1030	1075
Wheel base mm	2900	2900
Wheel track mm	1850	1850
Min ground clearance mm	365	365
Overall length mm	7250	7450
Overall height mm	3100	3100
Bucket width mm	2482	2482
Dumping angle (°)	45	45
Max breakout force kN	125±5	120±5
Max tractive force kN	95±5	95±5
Center of tyre (turning radius) mm	5100	5100
Boom lifting time S	≤5.0	≤5.0
Total cycle time S	≤8.5	≤8.5
Engine	Nominal power KW	92
	Nominal speed r/min	2200
Travel speed Km/h	1 forward/reverse gear	8/10
	2 forward/reverse gear	14/31
	3 forward gear	26
	4 forward gear	43

The technology of XCMG loader is subject to constant improvement and upgrading. In case the specifications or detailed appearance contained in this brochure differ from actual products, the latter shall prevail;

XCMG reserves the right of final interpretation for the above. Our products may be modified without prior notice to users.